INCEPTOR® IONA

Technical Specification

Product Code: OVCGEM6500 **Description:** 3 Hour Emergency Control Gear With Prewired Flow™ Connectors

General Information

Dimensions	330mm (L) x 50mm (W) x 40mm (D)
Materials	Housing: Polycarbonate
Product Weight	0.39Kg
Ingress Protection	IP20
Compatible Fittings	Inceptor® Iona Dimmable Range
Warranty	4 Years

Supply & Power

Input Voltage & Frequency	220-240V~ 50/60Hz
Electrical Safety	Class II (Double Insulated)
Ambient Temperature (Ta)	0°C - +40°C
Maximum Ambient Temperature	+45°C
Prewired Flow™ Connector	Yes (4 Pole CT205-F Push-fit Terminals)
Power Consumption	1W
Input Current	36mA
Charge Current	100mA
Output Voltage	33V
Output Power	1W
Open Circuit Voltage	33V
Earth Leakage Current	0mA
Battery Specification	4.8V 2000mAh Ni-MH
Battery Cell	4 Cell
Charging Time	24 Hours
Installation Requirements	Can bewired as Maintained or Non-maintained
Emergency Duration	3 Hours Minimum

IP20 4 Pre-wired flow™ Connector

OVIA Limited, 1 Scolmore Park, Landsberg, Lichfield Road Industrial Estate,
Tamworth, Staffordshire, B79 7XB United Kingdom
T: +44 (0)1827 300640
E: sales@oviaUK.com | **W:** oviaUK.com

Errors & Omissions excluded.
Specification is subject to change without notice.