


INCEPTOR® SLATE BACKLIT UGR

Technical Specification



Product Code: OV751301CWB

Description: 30W 600mm x 600mm Backlit Low-Glare LED Panel - 4000K - White



General Information

Dimensions	595mm (W) x 595mm (W) x 33mm (D)
Materials	Frame: Powdercoated Aluminium Diffuser: Polystyrene Back Cover: Powdercoated Steel
Finish	White (RAL 9003)
Product Weight	1.9Kg
Dimmable	No
Ingress Protection	IP20
Flammability Rating	TP(a)
IK Rating	IK06
Warranty	5 Years

Accessories

OVEMCG50	3 Hour Emergency Pack
OVCGMF0001	240V~ 29-48W Multi-function Dimmable Constant Current LED Driver (36W Setting)
OVSUSP731	Suspension Wire Kit
OVREC731	600mm x 600mm Recess Frame Kit

Supply & Power

Input Voltage & Frequency	220-240V~ 50Hz
Electrical Safety	Class II (Double Insulated)
Circuit Wattage	30W
Input Current	125mA
In-rush Current	< 40A (350uS@220V~)
Power Factor	> 0.9
Ambient Temperature (Ta)	-25°C - +45°C
Critical Temperature	+90°C
LED Driver	Remote Driver Supplied
Prewired Flow™ Connector	Yes (3 Pole CT105-F Push-fit Terminals)

Luminaire Output

Colour Temperature	4000K
CRI	>80
Typical Luminous Flux	3150lm
Efficacy	105lm/W
Beam Angle	120°
Unified Glare Rating (UGR)	<19
LED Lifetime (L70)	50,000 Hours
Flicker Free	No

Additional Information

Suspension hooks pre-fitted to the back

