

### General Information

Materials	Body: Powder Coated Aluminium; Diffuser: Polycarbonate
Colour	Black
Product Weight (Kg)	0.33
Ingress Protection	IP65
Impact Rating (IK)	06
Flammability Rating	UL94-V2
Mounting	Wall
Warranty (Years)	3

### Supply & Power Information

Continuous Operating Voltage (AC) (Hz)	220-240 (50)
Safety Class	I
Circuit Wattage (W)	50
Input Current (mA)	217
Inrush Current/Time	8.64A (0.076ms)
Power Factor	>0.9
Operating Temperature (°C)	+25
Input Mains Cable	3 x 1mm <sup>2</sup> H05RN-F (1 Metre)

### Luminaire Output


Colour Temperature (K)	3000
Colour Render Index (CRI)	>80
Typical Luminous Flux (lm)	4250
Efficacy (lm/W)	85
Beam Angle (°)	100
LED Lifetime (L70) (Hours)	20000

### Sensor Information

Maximum Mounting Height (m)	2.5
Detection Distance (m)	8
Detection Angle (°)	120
Light Level Settings (Lux)	10 to 2000
Time Delay Settings	10 Secs to 3 Mins

### Dimming Information

Dimmable	No
----------	----



OVIA Limited, Scolmore House, Mariner, Lichfield Road Industrial Estate,  
Tamworth, Staffordshire, B79 7UL United Kingdom

T: +44 (0)1827 300640

E: sales@oviaUK.com | W: oviaUK.com



Catalogue



Section



DoC



Installation

