


Product Code: OV80152EM

Description: 57W 1500mm Linear Utility LED Light With Emergency - IP65




General Information

Dimensions	1500mm (L) x 96mm (W) x 83mm (D)
Materials	Base: Polycarbonate Frosted Diffuser: Polycarbonate
Base Finish	Light Grey
Product Weight	2.03Kg
Dimmable	No
Ingress Protection	IP65
IK Rating	IK08
Mounting	Ceiling, Wall or Suspended
Warranty	5 Years

Accessories

OVEMB6430LIS	6.4V 3000mAh LiFePo4 Serial Battery - Serial
--------------	--



Supply & Power

Input Voltage & Frequency	220-240V~ 50/60Hz
Electrical Safety	Class I
Input Power	57W
Input Current	285mA
Inrush Current	8A (404ms)
Power Factor	>0.9
Ambient Temperature (Ta)	0°C - +40°C
Critical Temperature	+90°C
Terminations	5 Pole Push Fit Terminal Block
Cable Input Component	20mm IP68 Nylon Gland Supplied
Fixing Components	Surface and Suspension Brackets Supplied

Luminaire Output

Colour Temperature	4000K
CRI	>80
Typical Luminous Flux	6600lm
Efficacy	116lm/W
Beam Angle	105°
LED Lifetime (L70)	50,000 Hours
Fixing Components	Surface and Suspension Brackets Supplied

Emergency Information

Installation Requirements	Can be wired as maintained or non-maintained
Battery Specification	6.4V 3000mAh LiFePo4
Emergency Duration	3 Hours Minimum
Battery Warranty	4 Years
Emergency Light Level	400lm